



# HYDROTAP G5 BHA100 CELSIUS CUBE CHROME



BOILING

FILTERED



HOT & AMBIENT

UNFILTERED



## Order Code H59707Z00AU

Zip HydroTap Design Range CELSIUS Boiling Filtered water, plus Hot and Cold washing up water from a single tap. The system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including boiling water safety mode, 3 energy saving modes including ON/OFF timers and 2 hour sleep mode, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, and 0.2 micron water filtration.

Manufacturing Code H59707Z00AU

Capacity Commercial

Boiling Cups per hour 240

Tap Zip HydroTap Design Range CELSIUS CUBE Tap (Chrome)

Water Pressure Min 200kPa - Max 700kPa

Water Connection 1/2" BSP (G1/2)

Water Supply Requirements Cold and Hot

Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve

Power Rating 1.8kW 220-240V 50Hz

Booster Power Rating Zip HydroTap Booster 2.2kW 220-240V 50/60Hz

Power Supply 2 x 10 Amp socket outlets

Dimensions W280mm x D313mm x H333mm

Product Approvals

WaterMark, RCM

Wels Rating

5 Star, 5.5 litres

Warranty

5 years (appliance warranty 36 months plus additional 24 months tank warranty)

## Installation Requirements

'1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations. 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product. 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation. 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service. 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit. 6. Installation by Zip Professional Service can be arranged with a phone call or through [www.zipwater.com](http://www.zipwater.com)'

## Installation Detail

EKL2 HydroTap G5 v1.00 02 21 B, BA

<p><b>Ventilation requirements</b> Contact your local service provider if ventilation is not suitable</p> <p><b>Clearance envelope</b> Position the Tap and the Command Centre as close together as possible.</p>		<p><b>HydroTap Tap options</b></p> <p><b>Celsius Arc Tap</b></p>		<p><b>Celsius Cube Tap</b></p>	
<p><b>Tap Positioning</b> Position the Tap to dispense into the sink, allowing clearance for a cup or teapot.</p> <p>Ø35mm hole for Tap</p>		<p><b>Mains hot water supply installation</b> Hot and cold water supply required</p>			
<p><b>Tap Positioning</b> (continued)</p>		<p><b>HydroTap G5</b> <b>B Home, B60, B100</b> shown with Celsius Arc Tap</p>			

SCALE 1:5  
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.

