



HYDROTAP G5 BHA100 CELSIUS CUBE GUNMETAL



BOILING

FILTERED



HOT & AMBIENT

UNFILTERED



Order Code H59707Z09AU

Zip HydroTap Design Range CELSIUS Boiling Filtered water, plus Hot and Cold washing up water from a single tap. The system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including boiling water safety mode, 3 energy saving modes including ON/OFF timers and 2 hour sleep mode, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, and 0.2 micron water filtration.

Manufacturing Code H59707Z09AU

Capacity Commercial

Boiling Cups per hour 240

Tap Zip HydroTap Design Range CELSIUS CUBE Tap (Gunmetal)

Water Pressure Min 200kPa - Max 700kPa

Water Connection 1/2" BSP (G1/2)

Water Supply Requirements Cold and Hot

Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve

Power Rating 1.8kW 220-240V 50Hz

Booster Power Rating Zip HydroTap Booster 2.2kW 220-240V 50/60Hz

Power Supply 2 x 10 Amp socket outlets

Dimensions	W280mm x D313mm x H333mm
Product Approvals	WaterMark, RCM
Wels Rating	5 Star, 5.5 litres
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

Installation Requirements

'1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations. 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product. 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation. 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service. 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit. 6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com'

Installation Detail

DKL2 HydroTap G5 v1.00 02.21 B, BA

Ventilation requirements

Contact your local service provider if ventilation is not suitable

Clearance envelope

Position the Tap and the Command Centre as close together as possible.

HydroTap Tap options

Celsius Arc Tap

Celsius Cube Tap

Tap Positioning

Position the Tap to dispense into the sink, allowing clearance for a cup or teapot.

Ø35mm hole for Tap

4mm buffer pad air space

Clearance Envelope

Booster (B100 models)
NOTE: Not shown to scale. The 50mm hoses supplied with the Booster cannot be lengthened.

Mains cold water isolation valve (not supplied)

Air inlet grille

IEC Flex & Plug 230-240V, 50Hz power outlet

50 min. 280 50 min.

Mains hot water supply installation

Hot and cold water supply required

35mm hole in sink/benchtop for mixer tap

RED marked braided hose to mixer tap

Hot water isolation valve (not supplied)

BLUE marked braided hose

Braided hose to HydroTap Command Centre MAINS inlet

Mains water isolation valve (not supplied)

HydroTap G5

B Home, B60, B100

shown with Celsius Arc Tap

SCALE 1:5
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.

