



HYDROTAP G5 CHA100 CELSIUS CUBE MATTE BLACK



CHILLED

FILTERED



HOT & AMBIENT

UNFILTERED



Order Code H59711Z03AU

Zip HydroTap Design Range CELSIUS Chilled Filtered water, plus Hot and Cold washing up water from a single tap. The system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including 3 energy saving modes including ON/OFF timers and 2 hour sleep mode, 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, and 0.2 micron water filtration. Easy to install integrated ventilation tray included.

Manufacturing Code H59711Z03AU

Capacity Commercial

Chilled Cups per hour 175

Tap Zip HydroTap Design Range CELSIUS CUBE Tap (Matte Black)

Water Pressure Min 172kPa - Max 700kPa

Water Connection 1/2" BSP (G1/2)

Water Supply Requirements Cold and Hot

Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve

Power Rating 0.34kW 220-240V 50Hz

Power Supply 1 x 10 Amp socket outlet

Dimensions	W280mm x D476mm x H333mm
Product Approvals	WaterMark, RCM, ARC
Wels Rating	5 Star, 5.5 litres
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations. 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product. 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation. 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service. 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit. 6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com

Installation Detail

ENL2 HydroTap G5 v1.00 02.21 C40 C100

Ventilation requirements Contact your local service provider if ventilation is not suitable

Clearance envelope
Position the Tap and the Command Centre as close together as possible.

Vent tray (kit no. 93541)

Detail A. Air inlet grille
Cut-out in cabinet floor

Detail B. Vent Tray air outlet
Cut-out in cabinet floor

Tap Positioning
Position the Tap to dispense into the sink, allowing clearance for a cup or teapot.

Clearance Envelope

HydroTap Tap options

Celsius Arc Tap

Celsius Cube Tap

Mains hot water supply installation
Hot and cold water supply required

HydroTap G5
C40, C100
shown with Celsius Arc Tap

SCALE 1:5
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.

