



HYDROTAP G5 ULTRACARE BCU40 UV NON-CARBON FILTER CLASSIC PLUS TAP CHROME



BOILING



CHILLED

FILTERED

Order Code H557U1Z00AUC

Zip HydroTap UltraCare Boiling, Chilled Filtered water system features antimicrobial protection impregnated into key water paths for enhanced hygiene, LED UV-C disinfection, 0.2 micron carbon free internal filtration, Life cycle maintenance plan in a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including boiling water safety mode, 2 energy saving modes including ON/OFF timers and 2 hour sleep mode, 'Quiet' mode with automated intelligent fan speed adjustment, and 100% water efficient air cooled technology. Easy to install integrated ventilation tray included.



| | |
|-----------------------|--------------|
| Manufacturing Code | H557U1Z00AUC |
| Capacity | Commercial |
| Boiling Cups per hour | 160 |
| Chilled Cups per hour | 125 |

| | |
|---------------------------|--|
| Tap | Zip HydroTap CLASSIC PLUS Tap (Chrome) |
| Water Pressure | Min 170kPa - Max 700kPa |
| Water Connection | 1/2" BSP (G1/2) |
| Water Supply Requirements | Cold |
| Water Valves | Integrated 500kPa Pressure limiting valve and Dual Check Valve |
| Power Rating | 1.97kW 220-240V 50Hz |

| | |
|-------------------|--|
| Power Supply | 2 x 10 Amp socket outlet |
| Dimensions | W395mm x D464mm x H333mm |
| Product Approvals | WaterMark, RCM, ARC |
| Warranty | 5 years (appliance warranty 36 months plus additional 24 months tank warranty) |

Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1 metre of the product.
3. Zip Micro is air-cooled so discrete cabinetry cut-outs are required for ventilation.
4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com/book-service-visit

Installation Detail

ENCL 2 HydroTap 000001 00 02 21

| Ventilation requirements | HydroTap Tap options | Font options | Mixer Tap options |
|--|---|---|--|
| <p>Clearance envelope Position the Tap and the Command Centre as close together as possible.</p> <p>Vent tray (kit no. 93540)</p> <p>Detail A. Air inlet grille Cut-out in cabinet floor</p> <p>Detail B. Vent Tray air outlet Cut-out in cabinet floor</p> | <p>Touch-Free Wave</p> <p>Classic</p> <p>Classic Accessible</p> <p>Dispensing distance for all taps</p> | <p>Raised Font with 135mm Extension</p> <p>Cutting detail</p> | <p>Classic Mixer Tap</p> <p>Accessible Mixer Tap</p> <p>Vented mixer tap installation Only cold water supply required</p> |
| <p>Tap Positioning Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount on a Font (available as an accessory).</p> <p>Classic Accessible Mixer Tap (vented H option)</p> <p>Classic Plus Tap</p> <p>Clearance Envelope</p> <p>IEC Flex & Plug 230-240V, 10A, 50Hz power outlet</p> <p>Air inlet 50 min.</p> <p>Vent tray Hole should not be impeded by pipework</p> <p>Mains cold water isolation valve (not supplied)</p> <p>SCALE 1:5 ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.</p> | <p>Font with 135mm Extension</p> <p>Cutting detail</p> | <p>HydroTap G5 BCU40, BCU40 H UltraCare</p> <p>with "Classic Plus" Tap and Classic Accessible Mixer Tap (V)</p> | |

