



# HYDROTAP G5 ULTRACARE BCU60 UV NON-CARBON FILTER CLASSIC PLUS CHROME



BOILING

CHILLED

FILTERED

## Order Code H557U2Z00AUC

Zip HydroTap UltraCare Boiling, Chilled Filtered water system features antimicrobial protection impregnated into key water paths for enhanced hygiene, LED UV-C disinfection, 0.2 micron carbon free internal filtration, Life cycle maintenance plan in a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including boiling water safety mode, 2 energy saving modes including ON/OFF timers and 2 hour sleep mode, 'Quiet' mode with automated intelligent fan speed adjustment, and 100% water efficient air cooled technology. Easy to install integrated ventilation tray included.



Manufacturing Code	H557U2Z00AUC
Capacity	Commercial
Boiling Cups per hour	160
Chilled Cups per hour	175

Tap	Zip HydroTap CLASSIC PLUS Tap (Chrome)
Water Pressure	Min 170kPa - Max 700kPa
Water Connection	1/2" BSP (G1/2)
Water Supply Requirements	Cold
Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
Power Rating	2.1kW220-240 50Hz

Power Supply	2 x 10 Amp socket outlet
Dimensions	W395mm x D464mm x H333mm
Product Approvals	WaterMark, RCM, ARC
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

## Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1 metre of the product.
3. Zip Micro is air-cooled so discrete cabinetry cut-outs are required for ventilation.
4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
6. Installation by Zip Professional Service can be arranged with a phone call or through [www.zipwater.com/book-service-visit](http://www.zipwater.com/book-service-visit)

## Installation Detail

ENCL 2 HydroTap 000991 00 02 21

Ventilation requirements	HydroTap Tap options	Font options	Mixer Tap options
<p><b>Clearance envelope</b> Position the Tap and the Command Centre as close together as possible.</p> <p><b>Vent tray (kit no. 93540)</b></p> <p><b>Detail A. Air inlet grille</b> Cut-out in cabinet floor</p> <p><b>Detail B. Vent Tray air outlet</b> Cut-out in cabinet floor</p>	<p><b>Touch-Free Wave</b></p> <p><b>Classic</b></p> <p><b>Classic Accessible</b></p> <p><b>Dispensing distance for all taps</b></p>	<p><b>Raised Font with 135mm Extension</b></p> <p><b>Cutting detail</b></p>	<p><b>Classic Mixer Tap</b></p> <p><b>Accessible Mixer Tap</b></p> <p><b>Vented mixer tap installation</b> Only cold water supply required</p>
<p><b>Tap Positioning</b> Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount on a Font (available as an accessory).</p> <p><b>Classic Accessible Mixer Tap (vented H option)</b></p> <p><b>Classic Plus Tap</b></p> <p><b>Clearance Envelope</b></p> <p><b>IEC Flex &amp; Plug</b> 230-240V, 10A, 50Hz power outlet</p> <p><b>Air inlet</b> 50 min.</p> <p><b>Vent tray</b> Hole should not be impeded by pipework</p> <p><b>Mains cold water isolation valve</b> (not supplied)</p>	<p><b>Font with 135mm Extension</b></p> <p><b>Cutting detail</b></p>	<p><b>HydroTap G5</b> <b>BCU40, BCU40 H UltraCare</b></p> <p>with "Classic Plus" Tap and Classic Accessible Mixer Tap (V)</p>	

SCALE 1:5  
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.

