



# HYDROTAP G5 BHA100 3-IN-1 CLASSIC PLUS TAP WITH CUBE MIXER GUNMETAL



BOILING

FILTERED



HOT & AMBIENT

UNFILTERED



## Order Code H55957Z09AU

Zip HydroTap Classic Plus 3 in 1 Boiling Filtered water plus Hot and Cold washing up water from two separate taps. The system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including 2 boiling water safety modes, 3 energy saving modes including ON/OFF timers and sensor activated 'sleep when it's dark', 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, and 0.2 micron water filtration.

Manufacturing Code H55957Z09AU

Capacity Commercial

Boiling Cups per hour 240

Tap Zip HydroTap CLASSIC PLUS Tap (Gunmetal)

Water Pressure Min 300kPa - Max 700kPa

Water Connection 1/2" BSP (G1/2)

Water Supply Requirements Cold

Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve

Power Rating 1.8kW 220-240V 50Hz

Booster Power Rating Zip HydroTap Booster 2.2kW 220-240V 50/60Hz

Power Supply	2 x 10 Amp socket outlets
Dimensions	W280mm x D313mm x H333mm
Product Approvals	WaterMark, RCM
WELS Rating	5 Star, 5.5 litres
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

## Installation Requirements

'1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations. 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product. 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation. 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service. 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit. 6. Installation by Zip Professional Service can be arranged with a phone call or through [www.zipwater.com](http://www.zipwater.com)'

## Installation Detail

BKL2 HydroTap G5 v1.00 02.21 B, BA

### Ventilation requirements

Contact your local service provider if ventilation is not suitable

**Clearance envelope**  
Position the Tap and the Command Centre as close together as possible.

### HydroTap Tap options

Classic Plus: 216mm height, 126mm depth  
 Classic: 208mm height, 126mm depth  
 Elite Plus: 221mm height, 135mm depth  
 Touch-Free Wave: 214mm height, 126mm depth

### Mixer Tap options

**Arc Mixer Tap**: 256mm width, 220mm depth, 266mm height, 146mm depth, 434mm total height, 45° angle, 86mm offset, 51mm offset, 49mm hole.

**Cube Mixer Tap**: 256mm width, 218mm depth, 266mm height, 146mm depth, 362mm total height, 45° angle, 86mm offset, 73mm offset, 49mm hole.

35mm hole on sink or benchtop

### Tap Positioning

Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount the HydroTap Tap on a Font (available as an accessory).

35mm hole for HydroTap Tap      35mm hole for Mixer Tap

### Vented mixer tap installation

Only cold water supply required

35mm hole in sink/benchtop for mixer tap

WHITE marked braided hose

RED marked braided hose to HydroTap Command Centre MIXER OUT

BLUE marked braided hose to HydroTap Command Centre MIXER IN

Braided hose to HydroTap Command Centre MAINS inlet

Mains water isolation valve (not supplied)

4mm buffer pad air space

Clearance Envelope

Classic Plus Tap

Vented Arc Mixer Tap (optional)

216mm height

464mm height

200 min. height

333mm depth

50 min. distance

280mm distance

50 min. distance

Mains cold water isolation valve (not supplied)

Tee piece

Air inlet grille

IEC Flex & Plug 230-240V, 50Hz power outlet

313mm width

**HydroTap G5  
B60 H, B100 H**

shown with "Classic Plus" Tap and Arc Mixer Tap (V)

SCALE 1:5  
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.

