



HYDROTAP G5 CS100 CUBE BRUSHED ROSE GOLD



CHILLED



SPARKLING

FILTERED

Order Code H53765Z05AU

Zip HydroTap Design Range Chilled, Sparkling, Filtered water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including 3 energy saving modes including ON/OFF timers and 2 hour sleep mode, 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, 0.2 micron water filtration, and a refillable CO2 cylinder. Easy to install integrated ventilation tray included.



Manufacturing Code H53765Z05AU

Capacity Commercial

Combined Chilled and Sparkling Cups per hour 175

Tap Zip HydroTap Design Range CUBE Tap (Brushed Rose Gold)

Water Pressure Min 250kPa - Max 700kPa

Water Connection 1/2" BSP (G1/2)

Water Supply Requirements Cold

Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve

Power Rating 0.37kW 220-240V 50Hz

Power Supply 1 x 10 Amp socket outlet

Dimensions

W280mm x D480mm x H333mm

Product Approvals

WaterMark, RCM, ARC

Warranty

5 years (appliance warranty 36 months plus additional 24 months tank warranty)

Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations. 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product. 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation. 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service. 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit. 6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com

Installation Detail

BKL2 HydroTap G5 v1.00 02.21 CS100

Ventilation requirements Contact your local service provider if ventilation is not suitable

Clearance envelope
Position the Tap and the Command Centre as close together as possible.

200
333
50
Command Centre width

Vent tray (kit no. 93541)

520
496
40mm adjustment
40

HydroTap Tap options

HydroTap Arc Tap

20 162 305-333 40 175-225 115 194

Standalone Font with Arc Tap

162 333 225 223 174 40 176

HydroTap Cube Tap

20 162 276-326 40 175-225 115 194

Detail A. Air inlet grille
Cut-out in cabinet floor

326 40

Detail B. Vent Tray air outlet
Cut-out in cabinet floor

450 40

Tap Positioning
Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount on a Font (available as an accessory).

335mm hole for HydroTap Arc

200 min. 333 40 280 50 min. 476

IEC Flex & Plug 230-240V, 50Hz power outlet
CO₂ gas cylinder
Mains cold water isolation valve (not supplied) 50 min.
Air inlet grille
Vent tray
Note: should not be impeded by pipework

Cutting detail

174 for HydroTap Arc/Cube
3-off, 10 holes @ 145mm PCD, equispaced
140 hole for bowl
176 outline of font
35 hole for tap

**HydroTap G5
CS100**
shown with HydroTap Arc

