



HYDROTAP G5 ULTRACARE BCU60 UV NON-CARBON FILTER TOUCH-FREE WAVE CHROME



BOILING



CHILLED

FILTERED

Order Code H5W7U2Z00AUC

Zip HydroTap UltraCare Boiling, Chilled Filtered water system features antimicrobial protection impregnated into key water paths for enhanced hygiene, LED UV-C disinfection, 0.2 micron carbon free internal filtration, Life cycle maintenance plan in a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including boiling water safety mode, 2 energy saving modes including ON/OFF timers and 2 hour sleep mode, 'Quiet' mode with automated intelligent fan speed adjustment, and 100% water efficient air cooled technology. Easy to install integrated ventilation tray included.



Manufacturing Code	H5W7U2Z00AUC
Capacity	Commercial
Boiling Cups per hour	160
Chilled Cups per hour	175

Tap	Zip HydroTap Touch-Free Wave Tap (Chrome)
Water Pressure	Min 170kPa - Max 700kPa
Water Connection	1/2" BSP (G1/2)
Water Supply Requirements	Cold
Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
Power Rating	2.1kW220-240 50Hz

Power Supply	2 x 10 Amp socket outlet
Dimensions	W395mm x D464mm x H333mm
Product Approvals	WaterMark, RCM, ARC
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1 metre of the product.
3. Zip Micro is air-cooled so discrete cabinetry cut-outs are required for ventilation.
4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com/book-service-visit

Installation Detail

ENCL 2 HydroTap 000001 00 02 21

Ventilation requirements	HydroTap Tap options	Font options	Mixer Tap options
<p>Clearance envelope Position the Tap and the Command Centre as close together as possible.</p> <p>Vent tray (kit no. 93540) 520mm length, 496mm width, 40mm adjustment.</p> <p>Detail A. Air inlet grille Cut-out in cabinet floor. Dimensions: 40mm height, 326mm width.</p> <p>Detail B. Vent Tray air outlet Cut-out in cabinet floor. Dimensions: 450mm width.</p>	<p>Touch-Free Wave 214mm height.</p> <p>Classic 208mm height.</p> <p>Classic Accessible 219mm height.</p> <p>Dispensing distance for all taps 116mm.</p>	<p>Raised Font with 135mm Extension 116mm, 260mm, 351mm, 116mm, 268mm, 20mm, 152mm, 116mm, 164mm.</p> <p>Cutting detail Ø10 for M6 stud, Ø86 hole for bowl, Ø35 hole for tap.</p>	<p>Classic Mixer Tap 198mm, 233mm, 270mm, 224mm, Ø56mm.</p> <p>Accessible Mixer Tap 165mm, 250mm, 198mm, 233mm, 270mm, Ø56mm.</p> <p>Vented mixer tap installation Only cold water supply required.</p> <p>35mm hole in sink/benchtop for mixer tap.</p> <p>RED marked braided hose to HydroTap Command Centre MIXER OUT.</p> <p>BLUE marked braided hose to HydroTap Command Centre MIXER IN.</p> <p>WHITE marked braided hose to HydroTap Command Centre MAINS inlet.</p> <p>Mains water isolation valve (not supplied).</p>
<p>Tap Positioning Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount on a Font (available as an accessory).</p> <p>Ø35mm hole for HydroTap Tap.</p> <p>Classic Accessible Mixer Tap (vented H option) 216mm, 250mm, 4mm buffer pad air space.</p> <p>Classic Plus Tap 216mm, 250mm, 333mm, 200mm, 40mm, 50mm, 395mm.</p> <p>Clearance Envelope 200mm, 333mm, 40mm, 50mm, 395mm.</p> <p>IEC Flex & Plug 230-240V, 10A, 50Hz power outlet.</p> <p>Air inlet 50mm.</p> <p>Vent tray Note: should not be impeded by pipework.</p> <p>Mains cold water isolation valve (not supplied).</p> <p>SCALE 1:5 ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.</p>	<p>Font with 135mm Extension 116mm, 260mm, 351mm, 116mm, 104mm, 6mm, 219mm.</p> <p>Cutting detail Ø108 hole for bowl, Ø35 hole for tap, Ø10 for M6 stud.</p>	<p>HydroTap G5 BCU40, BCU40 H UltraCare</p> <p>with "Classic Plus" Tap and Classic Accessible Mixer Tap (V)</p>	

