



HYDROTAP G5 BC20 ARC BRUSHED CHROME



BOILING

CHILLED

FILTERED

Order Code H52702Z01AU

Zip HydroTap Design Range Boiling, Chilled, Filtered water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including boiling water safety mode, 3 energy saving modes including ON/OFF timers and 2 hour sleep mode, 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, and 0.2 micron water filtration.



Manufacturing Code H52702Z01AU

Capacity Commercial

Boiling Cups per hour 100

Chilled Cups per hour 75

Tap Zip HydroTap Design Range ARC Tap (Brushed Chrome)

Water Pressure Min 170kPa - Max 700kPa

Water Connection 1/2" BSP (G1/2)

Water Supply Requirements Cold

Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve

Power Rating 1.9kW 220-240V 50Hz

Power Supply 1 x 10 Amp socket outlet

Dimensions W280mm x D455mm x H333mm

Installation Requirements

'1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations. 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product. 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation. 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service. 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit. 6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com'

Installation Detail

BKL2 HydroTap G5 v1.00 02.21 BC BC20

Ventilation requirements Contact your local service provider if ventilation is not suitable

Clearance envelope
Position the Tap and the Command Centre as close together as possible.

200
333
50 Command Centre width 50

Air outlet louvre (if required)
Cut-out in door/wall, towards the top of the cabinet
285 60

Air inlet cut-out (required)
Cut-out in cabinet floor
max. 43 326

HydroTap Tap options

HydroTap Arc Tap

HydroTap Cube Tap

Standalone Font with Arc Tap

Cutting detail for HydroTap Arc/Cube

3-off, 10 holes @ 155mm PCD, equispaced
174 for HydroTap Arc/Cube
140 hole for bowl
176 outline of Font
35 hole for tap

Tap Positioning
Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount on a Font (available as an accessory).

Ø35mm hole for HydroTap Tap

4mm buffer pad air space

200 min.
333
50 min. 280 50 min.
455

Clearance Envelope
Clearance Envelope
Mains cold water isolation valve (not supplied)
Air inlet grille
IEC Flex & Plug 230-240V, 50Hz power outlet

HydroTap G5
BC Home, BC20
shown with HydroTap Arc

SCALE 1:5
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.

Tap Detail



