



# HYDROTAP G5 BC20 CLASSIC PLUS BRUSHED ROSE GOLD



BOILING

CHILLED

FILTERED

## Order Code H55702Z05AU

Zip HydroTap Classic Plus Boiling, Chilled, Filtered water features simple, intuitive controls including continuous flow to fill bottles, Boiling water safety lock, and SteriTouch® antimicrobial protection impregnated within the new Classic Plus touch-pad for enhanced hygiene. The water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including 2 boiling water safety modes, 3 energy saving modes including ON/OFF timers and sensor activated 'sleep when it's dark', 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, and 0.2 micron water filtration.



---

Manufacturing Code	H55702Z05AU
--------------------	-------------

---

Capacity	Commercial
----------	------------

---

Boiling Cups per hour	100
-----------------------	-----

---

Chilled Cups per hour	75
-----------------------	----

---

---

Tap	Zip HydroTap CLASSIC PLUS Tap (Brushed Rose Gold)
-----	---

---

Water Pressure	Min 170kPa - Max 700kPa
----------------	-------------------------

---

Water Connection	1/2" BSP (G1/2)
------------------	-----------------

---

Water Supply Requirements	Cold
---------------------------	------

---

<b>Water Valves</b>	Integrated 500kPa Pressure limiting valve and Dual Check Valve
<b>Power Rating</b>	1.9kW 220-240V 50Hz
<b>Power Supply</b>	1 x 10 Amp socket outlet
<b>Dimensions</b>	W280mm x D455mm x H333mm
<b>Product Approvals</b>	WaterMark, RCM, ARC
<b>Warranty</b>	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

## Installation Requirements

'1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations. 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product. 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation. 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service. 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit. 6. Installation by Zip Professional Service can be arranged with a phone call or through [www.zipwater.com](http://www.zipwater.com)'

## Installation Detail

BKL2 HydroTap G5 v1.01 03.21 BC BC20

Ventilation requirements	HydroTap Tap options	Font options
<p><b>Clearance envelope</b> Position the Tap and the Command Centre as close together as possible.</p> <p>200 333 50 Command Centre width</p>	<p><b>Classic Plus</b> 116 216 128 116 128 116 208 128 221 134</p> <p><b>Classic</b> 116 208 128 116 128 116 221 134</p> <p><b>Elite Plus</b> 112 221 134</p> <p><b>Touch-Free Wave</b> 116 214 128 100</p> <p>100mm clearance envelope required. For Sink installations, install on the left-hand side of the Sink for ease of access to Boiling water function.</p>	<p><b>Raised Font with 135mm Extension</b> part no. 95258</p> <p>116 260 116 268 351 20</p> <p><b>Font with 135mm Extension</b> part no. 90915</p> <p>116 260 116 219 351 6</p>
<p><b>Air outlet louvre (if required)</b> Cut-out in door/wall, towards the top of the cabinet</p> <p>285 60</p> <p><b>Air inlet cut-out (required)</b> Cut-out in cabinet floor</p> <p>max. 43 326</p>	<p><b>Tap Positioning</b> Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount the HydroTap on a Font (available as an accessory).</p> <p>35mm hole for HydroTap Tap</p> <p>Sink</p>	<p><b>Cutting detail</b></p> <p>10 for M6 stud 86 hole for bowl 35 hole for tap 116 164 152</p> <p><b>Cutting detail</b></p> <p>10 for M6 stud 108 hole for bowl 35 hole for tap 60 104 219</p>
<p>4mm buffer pad air space</p> <p>4mm buffer pad air space</p>		
<p>200 min. 333 50 min. 280 50 min. 455</p> <p>Classic Plus Tap 216</p> <p>Clearance Envelope</p> <p>Mains cold water isolation valve (not supplied)</p> <p>IEC Flex &amp; Plug 230-240V, 50Hz power outlet</p> <p>Air inlet grille</p>		
<p>SCALE 1:5 ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.</p>		

**HydroTap G5  
BC20**

shown with "Classic Plus" Tap

