



HYDROTAP G5 BHA100 3-IN-1 ELITE PLUS TAP WITH ARC MIXER BRUSHED CHROME



BOILING



HOT & AMBIENT

FILTERED

UNFILTERED

Order Code H5E857Z01AU

Zip HydroTap Design Range 3 in 1 Boiling Filtered water plus Hot and Cold washing up water from two separate taps. This water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including boiling water safety mode, 2 energy saving modes including ON/OFF timers and 2 hour sleep mode, 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, 0.2 micron water filtration, and 2 disposable CO2 cylinders.



Manufacturing Code	H5E857Z01AU
Capacity	Commercial
Number of people	100
Boiling Cups per hour	240

Tap	Zip HydroTap Design Range ELITE PLUS Tap (Brushed Chrome)
Water Pressure	Min 250kPa - Max 700kPa
Water Connection	1/2" BSP (G1/2)
Water Supply Requirements	Cold
Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
Power Rating	1.8kW 220-240V 50Hz

Booster Power Rating	Zip HydroTap Booster 2.2kW 220-240V 50/60Hz
Power Supply	2 x 10 Amp socket outlets
Dimensions	W280mm x D313mm x H333mm
Product Approvals	WaterMark, RCM, ARC
Wels Rating	5 Star, 5.5 litres
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations. 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product. 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation. 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service. 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit. 6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com

Installation Detail

EKL2 HydroTap G5 v1.01 03.21 B, BA

Ventilation requirements Contact your local service provider if ventilation is not suitable

Clearance envelope
Position the Tap and the Command Centre as close together as possible.

Air outlet louvre (if required)
Cut-out in door/wall, towards the top of the cabinet

Air inlet cut-out (required)
Cut-out in cabinet floor

HydroTap Tap options

Classic Plus (116mm height, 216mm depth, 126mm width, 46mm hole)

Classic (116mm height, 208mm depth, 126mm width, 46mm hole)

Elite Plus (112mm height, 221mm depth, 133mm width, 46mm hole)

Touch-Free Wave (116mm height, 214mm depth, 126mm width, 46mm hole)

100mm clearance envelope required. For Sink installations, install on the left-hand side of the Sink for ease of access to Boiling water function.

Tap Positioning
Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount the HydroTap Tap on a Font (available as an accessory).

35mm hole for HydroTap Tap 35mm hole for Mixer Tap

Mixer Tap options

Arc Mixer Tap
281mm width, 256mm depth, 220mm hole, 266mm height, 146mm depth, 49mm hole, 86mm offset, 434mm total height.

Cube Mixer Tap
281mm width, 256mm depth, 218mm hole, 266mm height, 146mm depth, 49mm hole, 86mm offset, 362mm total height.

35mm hole on sink or benchtop

Classic Mixer Tap
198mm height, 233mm width, 270mm depth, 224mm total height, 56mm hole.

Accessible Mixer Tap
250mm height, 188mm depth, 233mm width, 270mm depth, 56mm hole.

35mm hole on sink or benchtop

Vented mixer tap installation
Only cold water supply required

35mm hole in sink/benchtop for mixer tap

RED marked braided hose to HydroTap Command Centre MIXER OUT

BLUE marked braided hose to HydroTap Command Centre MIXER IN

WHITE marked braided hose

Braided hose to HydroTap Command Centre MAINS inlet

Mains water isolation valve (not supplied)

Booster (B100 models)
NOTE: Not shown to scale. The 500mm hoses supplied with the Booster cannot be lengthened.

200 min. height, 333mm total height, 50 min. width, 280mm width, 50 min. width, 186mm depth, 135mm depth, 216mm height, 464mm total height, 4mm buffer pad air space, 313mm width.

**HydroTap G5
B60 H, B100 H**

shown with "Classic Plus" Tap and Arc Mixer Tap (V)

SCALE 1:5
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.

