



# HYDROTAP G5 BHA100 3-IN-1 ELITE PLUS TAP WITH ARC MIXER BRUSHED GOLD



BOILING



HOT & AMBIENT

FILTERED

UNFILTERED

## Order Code H5E857Z07AU

Zip HydroTap Design Range 3 in 1 Boiling Filtered water plus Hot and Cold washing up water from two separate taps. This water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including boiling water safety mode, 2 energy saving modes including ON/OFF timers and 2 hour sleep mode, 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, 0.2 micron water filtration, and 2 disposable CO2 cylinders.



Manufacturing Code H5E857Z07AU

Capacity Commercial

Number of people 100

Boiling Cups per hour 240

Tap Zip HydroTap Design Range ELITE PLUS Tap (Brushed Gold)

Water Pressure Min 250kPa - Max 700kPa

Water Connection 1/2" BSP (G1/2)

Water Supply Requirements Cold

Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve

Power Rating 1.8kW 220-240V 50Hz

<b>Booster Power Rating</b>	Zip HydroTap Booster 2.2kW 220-240V 50/60Hz
<b>Power Supply</b>	2 x 10 Amp socket outlets
<b>Dimensions</b>	W280mm x D313mm x H333mm
<b>Product Approvals</b>	WaterMark, RCM, ARC
<b>Wels Rating</b>	5 Star, 5.5 litres
<b>Warranty</b>	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

## Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations. 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product. 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation. 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service. 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit. 6. Installation by Zip Professional Service can be arranged with a phone call or through [www.zipwater.com](http://www.zipwater.com)

## Installation Detail

EKL2 HydroTap G5 v1.01 03.21 B, BA

**Ventilation requirements** Contact your local service provider if ventilation is not suitable

**Clearance envelope**  
Position the Tap and the Command Centre as close together as possible.

200  
333  
50  
Command Centre width 50

**HydroTap Tap options**

Classic Plus: 116, 216, 126, 116, 208, 126, 221, 133, 112, 112, 133  
Classic: 116, 216, 126, 116, 208, 126, 221, 133  
Elite Plus: 116, 216, 126, 116, 208, 126, 221, 133  
Touch-Free Wave: 116, 214, 126, 100, 100

100mm clearance envelope required. For Sink installations, install on the left-hand side of the Sink for ease of access to Boiling water function.

**Mixer Tap options**

Arc Mixer Tap: 281, 256, 220, 220, 266, 146, 49, 86, 51, 434, 49, 86, 51, 434  
Cube Mixer Tap: 281, 256, 218, 266, 146, 49, 86, 73, 362, 49, 86, 73, 362  
Classic Mixer Tap: 198, 233, 270, 224, 198, 233, 270  
Accessible Mixer Tap: 165, 250, 198, 233, 270, 165, 250, 198, 233, 270

o35mm hole on sink or benchtop

**Tap Positioning**  
Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount the HydroTap Tap on a Font (available as an accessory).

o35mm hole for HydroTap Tap      o35mm hole for Mixer Tap

**Air outlet louvre (if required)**  
Cut-out in door/wall, towards the top of the cabinet

**Air inlet cut-out (required)**  
Cut-out in cabinet floor

**Vented Arc Mixer Tap (optional)**

4mm buffer pad air space

216, 464, 186, 135, 313

**Classic Plus Tap**

200 min., 333, 50 min., 280, 50 min.

**Booster (B100 models)**  
NOTE: Not shown to scale. The 500mm hoses supplied with the Booster cannot be lengthened.

Mains cold water isolation valve (not supplied)  
Air inlet grille  
IEC Flex & Plug 230-240V, 50Hz power outlet

**Vented mixer tap installation**  
Only cold water supply required

35mm hole in sink/benchtop for mixer tap  
RED marked braided hose to HydroTap Command Centre MIXER OUT  
BLUE marked braided hose to HydroTap Command Centre MIXER IN  
WHITE marked braided hose  
Braided hose to HydroTap Command Centre MAINS inlet  
Mains water isolation valve (not supplied)

**HydroTap G5  
B60 H, B100 H**

shown with "Classic Plus" Tap and Arc Mixer Tap (V)

SCALE 1:5  
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.

