



HYDROTAP G5 BHA100 3-IN-1 ELITE PLUS TAP WITH ARC MIXER GUNMETAL



BOILING



HOT & AMBIENT

FILTERED

UNFILTERED

Order Code H5E857Z09AU

Zip HydroTap Design Range 3 in 1 Boiling Filtered water plus Hot and Cold washing up water from two separate taps. This water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including boiling water safety mode, 2 energy saving modes including ON/OFF timers and 2 hour sleep mode, 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, 0.2 micron water filtration, and 2 disposable CO2 cylinders.



Manufacturing Code	H5E857Z09AU
--------------------	-------------

Capacity	Commercial
----------	------------

Number of people	100
------------------	-----

Boiling Cups per hour	240
-----------------------	-----

Tap	Zip HydroTap Design Range ELITE PLUS Tap (Gunmetal)
-----	---

Water Pressure	Min 250kPa - Max 700kPa
----------------	-------------------------

Water Connection	1/2" BSP (G1/2)
------------------	-----------------

Water Supply Requirements	Cold
---------------------------	------

Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
--------------	--

Power Rating	1.8kW 220-240V 50Hz
--------------	---------------------

Booster Power Rating	Zip HydroTap Booster 2.2kW 220-240V 50/60Hz
Power Supply	2 x 10 Amp socket outlets
Dimensions	W280mm x D313mm x H333mm
Product Approvals	WaterMark, RCM, ARC
Wels Rating	5 Star, 5.5 litres
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations. 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product. 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation. 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service. 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit. 6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com

Installation Detail

EKL2 HydroTap G5 v1.01 03.21 B, BA

Ventilation requirements Contact your local service provider if ventilation is not suitable

Clearance envelope
Position the Tap and the Command Centre as close together as possible.

Air outlet louvre (if required)
Cut-out in door/wall, towards the top of the cabinet

Air inlet cut-out (required)
Cut-out in cabinet floor

HydroTap Tap options

Classic Plus, Classic, Elite Plus, Touch-Free Wave

Tap Positioning
Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount the HydroTap Tap on a Font (available as an accessory).

35mm hole for HydroTap Tap 35mm hole for Mixer Tap

Mixer Tap options

Arc Mixer Tap

Cube Mixer Tap

Classic Mixer Tap

Accessible Mixer Tap

Vented mixer tap installation
Only cold water supply required

35mm hole in sink/benchtop for mixer tap

RED marked braided hose to HydroTap Command Centre MIXER OUT

WHITE marked braided hose

Braided hose to HydroTap Command Centre MAINS inlet

BLUE marked braided hose to HydroTap Command Centre MIXER IN

Mains water isolation valve (not supplied)

Booster (B100 models)
NOTE: Not shown to scale. The 500mm hoses supplied with the Booster cannot be lengthened.

Clearance Envelope

4mm buffer pad air space

Classic Plus Tap

Vented Arc Mixer Tap (optional)

Tea piece

Mains cold water isolation valve (not supplied)

Air inlet grille

IEC Flex & Plug 230-240V, 50Hz power outlet

SCALE 1:5
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.

**HydroTap G5
B60 H, B100 H**

shown with "Classic Plus" Tap and Arc Mixer Tap (V)

