



HYDROTAP G5 BHA60 3-IN-1 ELITE PLUS TAP WITH ARC MIXER MATTE BLACK



BOILING



HOT & AMBIENT

FILTERED

UNFILTERED

Order Code H5E856Z03AU

Zip HydroTap Design Range 3 in 1 Boiling Filtered water plus Hot and Cold washing up water from two separate taps. This water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including boiling water safety mode, 2 energy saving modes including ON/OFF timers and 2 hour sleep mode, 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, 0.2 micron water filtration, and 2 disposable CO2 cylinders.



Manufacturing Code H5E856Z03AU

Capacity Commercial

Number of people 60

Boiling Cups per hour 160

Tap Zip HydroTap Design Range ELITE PLUS Tap (Matte Black)

Water Pressure Min 250kPa - Max 700kPa

Water Connection 1/2" BSP (G1/2)

Water Supply Requirements Cold

Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve

Power Rating 1.8kW 220-240V 50Hz

Power Supply	1 x 10 Amp socket outlet
Dimensions	W280mm x D313mm x H333mm
Product Approvals	WaterMark, RCM, ARC
Wels Rating	5 Star, 5.5 litres
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations. 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product. 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation. 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service. 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit. 6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com

Installation Detail

BKL2 HydroTap G5 v1.01 03.21 B, BA

Ventilation requirements Contact your local service provider if ventilation is not suitable

Clearance envelope
Position the Tap and the Command Centre as close together as possible.

Tap Positioning
Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount the HydroTap Tap on a Font (available as an accessory).

35mm hole for HydroTap Tap 35mm hole for Mixer Tap

HydroTap Tap options

Mixer Tap options

Arc Mixer Tap
Dimensions: 281mm width, 256mm depth, 206mm height, 146mm depth, 220mm width, 434mm height, 86mm depth, 51mm depth, 49mm diameter hole.

Cube Mixer Tap
Dimensions: 281mm width, 256mm depth, 268mm height, 146mm depth, 218mm width, 362mm height, 86mm depth, 73mm depth, 49mm diameter hole.

Classic Mixer Tap
Dimensions: 198mm height, 233mm width, 270mm depth, 224mm height, 56mm diameter hole.

Accessible Mixer Tap
Dimensions: 165mm width, 250mm height, 198mm height, 233mm width, 270mm depth, 56mm diameter hole.

Vented mixer tap installation
Only cold water supply required

Clearance Envelope

Booster (B100 models)
NOTE: Not shown to scale. The 500mm hoses supplied with the Booster cannot be lengthened.

IEC Flex & Plug
230-240V, 50/60Hz power outlet

SCALE 1:5
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.

**HydroTap G5
B60 H, B100 H**

shown with "Classic Plus" Tap and Arc Mixer Tap (V)

