



HYDROTAP G5 BCHA100 4-IN-1 ELITE PLUS TAP WITH CLASSIC MIXER MATTE BLACK



BOILING



CHILLED



HOT & AMBIENT

FILTERED

UNFILTERED

Order Code H5E624Z03AU

Zip HydroTap Design Range 4 in 1 Boiling, Chilled, Filtered water plus Hot and Cold washing up water from two separate taps. This water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including boiling water safety mode, 2 energy saving modes including ON/OFF timers and 2 hour sleep mode, 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, 0.2 micron water filtration, and 2 disposable CO2 cylinders. Easy to install integrated ventilation tray included.



Manufacturing Code H5E624Z03AU

Capacity Commercial

Number of people 100

Boiling Cups per hour 240

Chilled Cups per hour 175

Tap Zip HydroTap Design Range ELITE PLUS Tap (Matte Black)

Water Pressure Min 250kPa - Max 700kPa

Water Connection 1/2" BSP (G1/2)

Water Supply Requirements Cold

Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
Power Rating	2.1kW 220-240V 50Hz
Booster Power Rating	Zip HydroTap Booster 2.2kW 220-240V 50/60Hz
Power Supply	2 x 10 Amp socket outlets
Dimensions	W395mm x D464mm x H333mm
Product Approvals	WaterMark, RCM, ARC
Wels Rating	6 Star, 3.0 litres
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations. 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product. 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation. 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service. 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit. 6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com

Installation Detail

DKL2 HydroTap G5 v1.01 03.21 BC40 BC60

Ventilation requirements Contact your local service provider if ventilation is not suitable

Clearance envelope
Position the Tap and the Command Centre as close together as possible.

Vent tray (kit no. 93540)

Detail A. Air inlet grille
Cut-out in cabinet floor

Detail B. Vent Tray air outlet
Cut-out in cabinet floor

HydroTap Tap options

Classic Plus (116mm height, 216mm width, 126mm depth, 46mm hole)

Classic (116mm height, 208mm width, 126mm depth, 46mm hole)

Elite Plus (112mm height, 221mm width, 134mm depth, 46mm hole)

Touch-Free Wave (116mm height, 214mm width, 126mm depth, 46mm hole)

100mm clearance envelope required. For Sink installations, install on the left-hand side of the Sink for ease of access to Boiling water function.

Tap Positioning
Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount the HydroTap Tap on a Font (available as an accessory).

35mm hole for HydroTap Tap

35mm hole for Mixer Tap

Mixer Tap options

Arc Mixer Tap
281mm width, 256mm depth, 220mm height, 265mm total height, 146mm base, 49mm hole, 86mm offset, 51mm offset, 434mm total height.

Cube Mixer Tap
281mm width, 256mm depth, 218mm height, 265mm total height, 146mm base, 49mm hole, 86mm offset, 73mm offset, 362mm total height.

35mm hole on sink or benchtop

Classic Mixer Tap
196mm height, 233mm width, 270mm depth, 224mm total height, 56mm hole.

Accessible Mixer Tap
250mm height, 196mm width, 233mm depth, 270mm total height, 56mm hole.

35mm hole on sink or benchtop

Vented mixer tap installation
Only cold water supply required

HydroTap G5
BC40 H, BC60 H, BC100 H

shown with "Classic Plus" Tap and Arc Mixer Tap (V)

SCALE 1:5
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.

