



HYDROTAP G5 BCSHA100 5-IN-1 ELITE PLUS TAP WITH CLASSIC MIXER BRUSHED CHROME



BOILING



CHILLED



SPARKLING



HOT & AMBIENT

FILTERED

UNFILTERED

Order Code H5E676Z01AU

Zip HydroTap Design Range 5 in 1 Boiling, Chilled, Sparkling, Filtered water plus Hot and Cold washing up water from two separate taps. This water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including boiling water safety mode, 2 energy saving modes including ON/OFF timers and 2 hour sleep mode, 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, 0.2 micron water filtration, and a refillable CO2 cylinder. Easy to install integrated ventilation tray included.



Manufacturing Code H5E676Z01AU

Capacity Commercial

Number of people 100

Boiling Cups per hour 240

Chilled Cups per hour 175

Tap Zip HydroTap Design Range ELITE PLUS Tap (Brushed Chrome)

Water Pressure Min 250kPa - Max 700kPa

Water Connection 1/2" BSP (G1/2)

Water Supply Requirements Cold

Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
Power Rating	2.15kW 220-240V 50Hz
Booster Power Rating	Zip HydroTap Booster 2.2kW 220-240V 50/60Hz
Power Supply	2 x 10 Amp socket outlets
Dimensions	W395mm x D464mm x H333mm
Product Approvals	WaterMark, RCM, ARC
Wels Rating	6 Star, 3.0 litres
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations. 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product. 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation. 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service. 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit. 6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com

Installation Detail

BKL2 HydroTap G5 v1.01 03.21 BCS60 BCS100

Ventilation requirements

Contact your local service provider if ventilation is not suitable

Clearance envelope
Position the Tap and the Command Centre as close together as possible.

Vent tray (kit no. 93540)

Detail A. Air inlet grille
Cut-out in cabinet floor

Detail B. Vent Tray air outlet
Cut-out in cabinet floor

HydroTap Tap options

Classic Plus 116mm height, 216mm depth, 126mm width, 46mm diameter base.

Classic 116mm height, 208mm depth, 126mm width, 46mm diameter base.

Elite Plus 112mm height, 221mm depth, 134mm width, 46mm diameter base.

Touch-Free Wave 116mm height, 214mm depth, 126mm width, 46mm diameter base.

100mm clearance envelope required. For Sink installations, install on the left-hand side of the Sink for ease of access to Boiling water function.

Tap Positioning

Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount the HydroTap Tap on a Font (available as an accessory).

35mm hole for HydroTap Tap 35mm hole for Mixer Tap

Mixer Tap options

Arc Mixer Tap

35mm hole on sink or benchtop

Cube Mixer Tap

35mm hole on sink or benchtop

Classic Mixer Tap

35mm hole on sink or benchtop

Accessible Mixer Tap

35mm hole on sink or benchtop

Vented mixer tap installation

Only cold water supply required

35mm hole in sink/benchtop for mixer tap

WHITE marked braided hose

Braided hose to HydroTap Command Centre MAINS inlet

RED marked braided hose to HydroTap Command Centre MIXER OUT

BLUE marked braided hose to HydroTap Command Centre MIXER IN

Mains water isolation valve (not supplied)

Booster (BCS100 models)
Note: The 500mm braided hoses supplied cannot be lengthened

IEC Flex & Plug 230-240V, 10A, 50Hz power outlet

Air inlet 50 min.

Vent tray Note: should not be impeded by pipework

Mains cold water isolation valve (not supplied)

SCALE 1:5

HydroTap G5

BCS60 H, BCS100 H

shown with "Classic Plus" Tap

