

Specifiers



HYDROTAP G5 BCS20 CLASSIC MATTE BLACK

Order Code H51760Z03AU



FILTERED

BOILING



FILTERED

CHILLED



FILTERED

SPARKLING

Zip HydroTap Boiling, Chilled, Sparkling, Filtered water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including 2 boiling water safety modes, 3 energy saving modes including ON/OFF timers and sensor activated 'sleep when it's dark', 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, 0.2 micron water filtration, and a refillable CO2 cylinder.



Manufacturing Code H51760Z03AU

Capacity Commercial

Disability Options Unavailable

Boiling Cups per hour 100

Combined Chilled and Sparkling Cups per hour 75

Specifications

[Specification Sheet](#)

Tap Zip HydroTap CLASSIC Tap (Matte Black)

Water Pressure Min 250kPa - Max 700kPa

Water Connection 1/2" BSP (G1/2)

Water Supply Requirements Cold

Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve

Power Rating 1.96kW 220-240V 50Hz

Power Supply 1 x 10 Amp socket outlet

| | |
|--------------------------|--|
| Dimensions | W339mm x D460mm x H333mm |
| Product Approvals | WaterMark, RCM, ARC |
| Warranty | 5 years (appliance warranty 36 months plus additional 24 months tank warranty) |

Download more resources

Click the icons below to download individual files

 [Download BIM Files](#)

Manuals

[Material Safety Data Sheet](#)

Brochures

Product Brochure

Certifications

Filter Performance Images

Filter Performance Data

Health Safety Image

Health Safety Download

Environment ISO Image

Environment ISO Download

Quality ISO Image

Quality ISO Download

ARC Image

ARC Download

CE Image

RCM Image

Watermark

Environmental Product Declaration Brochure

Environmental Product Declaration