



HYDROTAP G5 BCS60 CLASSIC BRUSHED CHROME



BOILING



CHILLED



SPARKLING

FILTERED

Order Code H51762Z01AU

Zip HydroTap Boiling, Chilled, Sparkling, Filtered water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including 2 boiling water safety modes, 3 energy saving modes including ON/OFF timers and sensor activated 'sleep when it's dark', 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, 0.2 micron water filtration, and a refillable CO2 cylinder. Easy to install integrated ventilation tray included.



Manufacturing Code H51762Z01AU

Capacity Commercial

Boiling Cups per hour 160

Combined Chilled and Sparkling Cups per hour 175

Tap Zip HydroTap CLASSIC Tap (Brushed Chrome)

Water Pressure Min 250kPa - Max 700kPa

Water Connection 1/2" BSP (G1/2)

Water Supply Requirements Cold

Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve

Power Rating	2.15kW 220-240V 50Hz
Power Supply	1 x 10 Amp socket outlet
Dimensions	W395mm x D464mm x H333mm
Product Approvals	WaterMark, RCM, ARC
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations. 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product. 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation. 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service. 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit. 6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com

Installation Detail

EKL2 HydroTap G5 v1.01 03.21 BCS60 BCS100

Ventilation requirements	HydroTap Tap options	Font options
<p>Contact your local service provider if ventilation is not suitable</p> <p>Clearance envelope Position the Tap and the Command Centre as close together as possible.</p> <p>Vent tray (kit no. 93540)</p>	<p>Classic Plus (116mm height, 216mm depth, 126mm width, 46mm diameter)</p> <p>Classic (116mm height, 208mm depth, 126mm width, 46mm diameter)</p> <p>Elite Plus (112mm height, 221mm depth, 133mm width, 46mm diameter)</p> <p>Touch-Free Wave (116mm height, 214mm depth, 126mm width, 46mm diameter)</p> <p>100mm clearance envelope required. For Sink installations, install on the left-hand side of the Sink for ease of access to Boiling water function.</p>	<p>Raised Font with 135mm Extension (part no. 95258)</p> <p>Font with 135mm Extension (part no. 90915)</p>
<p>Detail A. Air inlet grille Cut-out in cabinet floor</p> <p>Detail B. Vent Tray air outlet Cut-out in cabinet floor</p>	<p>Tap Positioning Position the Tap to dispense into the sink, allowing clearance for a cup or leapot. Alternatively, mount the HydroTap Tap on a Font (available as an accessory).</p> <p>35mm hole for HydroTap Tap</p>	<p>Cutting detail</p> <p>o10 for M6 stud, o86 hole for bowl, o35 hole for tap</p> <p>Cutting detail</p> <p>o108 hole for bowl, o35 hole for tap, o10 for M6 stud, o219 diameter</p>
<p>4mm buffer pad air space</p> <p>Classic Plus Tap</p> <p>Clearance Envelope</p> <p>Booster (BCS100 models) Note: The 500mm braided hoses supplied cannot be lengthened</p> <p>140mm, 186mm, 135mm, 200 min., 333mm, 40mm, 500mm, 50 min., 395mm, 50 min., 464mm</p> <p>IEC Flex & Plug 230-240V, 10A, 50Hz power outlet</p> <p>Air inlet 50 min.</p> <p>Vent tray Note: should not be impeded by pipework</p> <p>Main cold water isolation valve (not supplied)</p>		

SCALE 1:5
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.

HydroTap G5
BCS60, BCS100

shown with "Classic Plus" Tap

